

| | | |
|--|---|--|
| FORM PTO-1390 (REV 11-2000) | U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE | ATTORNEY'S DOCKET NUMBER 36-1537 |
| TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371 | | U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.5) 10/069295 |
| INTERNATIONAL APPLICATION NO. PCT/GB00/03678 | INTERNATIONAL FILING DATE 25 September 2000 | PRIORITY DATE CLAIMED 24 September 1999 |

TITLE OF INVENTION

PACKET NETWORK INTERFACING

APPLICANT(S) FOR DO/EO/US


HOVELL et al

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.
4. ☒ The U.S. has been elected by the expiration of 19 months from the priority date (Article 31).
5. A copy of the International Application as filed (35 U.S.C. 371(c)(2)).
 - a. ☒ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
 - a. ☐ is attached hereto.
 - b. ☐ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has **NOT** expired.
 - d. ☐ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11 To 20 below concern document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 C.F.R. 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 C.F.R. 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.
14. ☐ A SECOND or SUBSEQUENT preliminary amendment.
15. ☐ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821-1.825.
18. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
19. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
20. ☐ Other items or information.

| | |
|---|--|
| U.S. APPLICATION NO. (If known, give 37 C.F.R. 1.51) Unknown 659293 INTERNATIONAL APPLICATION NO. PCT/GB00/03678 | ATTORNEY'S DOCKET NUMBER 36-1537 |
| 21. <input checked="" type="checkbox"/> The following fees are submitted: | |
| BASIC NATIONAL FEE (37 C.F.R. 1.492(a)(1)-(5): -- Neither international preliminary examination fee (37 C.F.R. 1.482) nor international search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1040.00 -- International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$890.00 -- International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but international search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO \$740.00 -- International preliminary examination fee (37 C.F.R. 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$710.00 -- International preliminary examination fee (37 C.F.R. 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00 | |
| ENTER APPROPRIATE BASIC FEE AMOUNT = | |
| Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 C.F.R. 1.492(e)). | |
| CLAIMS NUMBER FILED NUMBER EXTRA RATE | |
| Total Claims 8 -20 = 0 X \$18.00 \$ 0.00 | |
| Independent Claims 2 -3 = 0 X \$84.00 \$ 0.00 | |
| MULTIPLE DEPENDENT CLAIMS(S) (if applicable) \$280.00 \$ 0.00 | |
| TOTAL OF ABOVE CALCULATIONS = | |
| <input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2. \$ 0.00 | |
| SUBTOTAL = | |
| Processing fee of \$130.00, for furnishing the English Translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 C.F.R. 1.492(f)). + 0.00 | |
| TOTAL NATIONAL FEE = | |
| Fee for recording the enclosed assignment (37 C.F.R. 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 C.F.R. 3.28, 3.31). \$40.00 per property + \$ 40.00 | |
| Fee for Petition to Revive Unintentionally Abandoned Application (\$1280.00 - Small Entity = \$640.00) \$ 0.00 | |
| TOTAL FEES ENCLOSED = | |
| Amount to be refunded \$ | |
| Charged \$ | |
| a. <input checked="" type="checkbox"/> A check in the amount of \$930.00 to cover the above fees is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. 14-1140 in the amount of \$_____ to cover the above fees. A duplicate copy of this form is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 14-1140. A duplicate copy of this form is enclosed. d. <input checked="" type="checkbox"/> The entire content of the foreign application(s), referred to in this application is/are hereby incorporated by reference in this application. | |
| NOTE: Where an appropriate time limit under 37 C.F.R. 1.494 or 1.495 has not been met, a petition to revive (37 C.F.R. 1.137(a) or (b)) must be filed and granted to restore the application to pending status. | |
| SEND ALL CORRESPONDENCE TO: NIXON & VANDERHYE P.C. 1100 North Glebe Road, 8 th Floor Arlington, Virginia 22201-4714 Telephone: (703) 816-4000 | |
|  SIGNATURE | |
| Larry S. Nixon NAME | |
| 25,640 February 25, 2002 REGISTRATION NUMBER Date | |

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of

HOVELL et alAtty. Ref.: **36-1537**Serial No. **Unknown**

Group:

National Phase of: **PCT/GB00/03678**International Filing Date: **25 September 2000**Filed: **February 25, 2002**

Examiner:

For: **PACKET NETWORK INTERFACING**

* * * * *

February 25, 2002Assistant Commissioner for Patents
Washington, DC 20231

Sir:

PRELIMINARY AMENDMENT

Prior to calculation of the filing fee and in order to place the above identified application in better condition for examination, please amend as follows:

IN THE SPECIFICATION

Page 1, after the title insert the following:

-- This application is the US national phase of international application

PCT/GB00/03678 filed 25 September 2000 which designated the U.S. --.

IN THE CLAIMS

Please substitute the following amended claim for corresponding claim previously presented. A copy of the amended claim showing the current revision is attached.

3. (Amended) A method as claimed in claim 1, including setting a time to live for a said stored mapping, and rendering that stored mapping unuseable upon the expiry of the time to live.

Cancel claims 9 and 10 without prejudice or disclaimer.

10069295.022502

HOVELL et al
Serial No. **Unknown**

REMARKS


Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached page is captioned "**Version with markings to show changes made.**"

The above amendments are made to place the claims in a more traditional format.

Respectfully submitted,

NIXON & VANDERHYE P.C.

By:



Larry S. Nixon
Reg. No. 25,640

LSN:Imy

1100 North Glebe Road, 8th Floor
Arlington, VA 22201-4714
Telephone: (703) 816-4000
Facsimile: (703) 816-4100

10069295 - 022502

VERSION WITH MARKINGS TO SHOW CHANGES MADE

3. (Amended) A method as claimed in [either claim 1 or claim 2] claim 1,
including setting a time to live for a said stored mapping, and rendering that stored
mapping unuseable upon the expiry of the time to life.

10069295.022502

6/p/r

PACKET NETWORK INTERFACING

This invention relates to the establishment of a tunnel entrance for packets crossing the border between a first network operating in accordance with a first transmission protocol and having network addresses in accordance with a first addressing convention, herein referred to as first type addresses, and a second network operating in accordance with a second transmission protocol and having network addresses in accordance with a second addressing convention, herein referred to as second type addresses, and relates particularly, but not exclusively, to communication between hosts in respective Internet Protocol version 6 (IPv6) domains separated by an Internet Protocol version 4 (IPv4) domain.

Herein, the terms packet and message are used interchangeably and have the same meaning, and the term Internet domain is used as a specific example of a network.

In Internet technology, it had become apparent that the initial transport protocol, IPv4, needed to be enhanced, principally to increase the available address space and add a hierarchical address structure. The result was IPv6 which has a simplified header format compared with IPv4, but which uses 128 bit addresses as compared with 32 bit addresses used in IPv4.

Readers wishing to have an overview of this general area might like to access a list of Internet-Drafts, which are working documents of the IETF, at <http://www.ietf.org/1id-abstracts.txt>, and a particularly relevant document is "A Guide to the Introduction of IPv6 in the IPv4 World" <draft-ietf-ngtrans-introduction-to-ipv6-transition-01.txt>, also referred to as "Guide to IPv6 Transition".

As mentioned, the present invention relates to tunnelling. Known tunnelling techniques are of two types: configured and automatic.

A configured tunnel is created by manual configuration of a tunnelling interface between an IPv6 domain and an IPv4 domain such that all packets received from the IPv6 domain are encapsulated in IPv4 packets addressed to a specific tunnel end point, i.e. the tunnelling interface between the IPv4 domain and the remote IPv6 domain containing the destination IPv6 host.

An automatic tunnel on the other hand does not need manual configuration: the tunnel end points are automatically determined. Several automatic tunnelling

20060225.022502

mechanisms are currently in development within the IETF, these being known in the art as, 6over4, 6to4, Dynamic Tunnelling, and Tunnel Broker.

For more detailed information on 6over4 the reader can obtain from the IETF, the document known as RFC2829, or any variant thereof, "Transmission of
5 IPv6 over IPv4 Domains without Explicit Tunnels", by B. Carpenter and C. Jung, March 1999.

For more detailed information on 6to4 the reader can obtain from the IETF, the document known as draft-ietf-ngtrans-6to4-02.txt, or any variant thereof, "Connection of IPv6 Domains via IPv4 Clouds without Explicit Tunnels", by B.
10 Carpenter and K. Moore.

For more detailed information on Dynamic Tunnelling the reader can obtain from the IETF, the document known as draft-ietf-ngtrans-dti-00.txt.

For more detailed information on Tunnel Broker the reader can obtain from the IETF, the document known as draft-ietf-ngtrans-broker-00.txt.

15 These known automatic tunnelling mechanisms use a variety of techniques to enable the tunnel to be automatically established:

- ξ 6over4 Multicast
- ξ 6to4 Special IPv6 address in which the top level aggregator (TLA) contains an identifier for the 6to4 tunnelling mechanism, and the next
20 level aggregator (NLA) contains the IPv4 address of the tunnel end point
- ξ Dynamic Tunnelling via DNS
- ξ Tunnel Broker www based tool

In accordance with a first aspect of the present invention, there is provided a method of establishing a tunnel from a first interface between a first network and
25 a second network to a second interface between the second network and a third network, the first and third networks operating in accordance with a first transmission protocol and having addresses in accordance with a first addressing convention, and the second network operating in accordance with a second transmission protocol and having addresses in accordance with a second addressing
30 convention, the tunnel being for the transport of messages from a first host on the first network to a second host on the third network, the method comprising the steps of:

10060295.022502

sending from the first host an address request message in accordance with the first transmission protocol, referred to herein as a first type address request message, containing the name of the second host;

upon receipt of the address request message at a name to address conversion system of the third network, returning an address response message in accordance with the first transmission protocol, referred to herein as a first type address response message, and containing the address of the second host in a response address field;

upon receipt of that first type address response message at the second interface,

converting it to an address response message in accordance with the second transmission protocol, referred to herein as a second type address response message, and

augmenting that converted second type address response message by fields respectively containing the address of the second interface in accordance with the second addressing convention and the address of the second host in accordance with the first addressing convention; and

upon receipt of that augmented that converted second type address response message at the first interface,

converting it to a first type address response message, retrieving the contents of the augmenting fields, storing at the first interface a mapping of the retrieved address of the second host and the retrieved address of the second interface for use in encapsulating messages from the first host addressed to the second host, and

replacing the content of the response address field of the resulting first type address response message by the retrieved address of the second host.

Preferably, for establishing a tunnel in the reverse direction for the transport of messages from the second host to the first host, the method comprises the further steps of:

10069205-0025001

upon receipt at the first interface of a message from the first host addressed to the second host, encapsulating that received message in accordance with the first mapping; and

upon receipt of the encapsulated message at the second interface,
5 un-encapsulating that received encapsulated message,
retrieving from the encapsulating header the address of the first interface in accordance with the second addressing convention,
retrieving from the un-encapsulated message the address of the first host in accordance with the first addressing convention, and
10 storing at the second interface a mapping of the retrieved address of the first host and the retrieved address of the first interface for use in encapsulating messages from the second host addressed to the first host.

There may be included the steps of setting a time to live for a said stored
15 mapping, and rendering that stored mapping unuseable upon the expiry of the time to live, preferably deleting that stored mapping.

In accordance with a second aspect of the present invention, there is provided a method of sending packets from a first host on a first network via a second network to a second host on a third network, the first and third networks
20 operating in accordance with a first transmission protocol and having addresses in accordance with a first addressing convention, and the second network operating in accordance with a second transmission protocol and having addresses in accordance with a second addressing convention, comprising the steps of:

establishing a tunnel from a first interface between the first network and the
25 second network to a second interface between the second network and the third network in accordance with the method of the first aspect of the present invention;

upon receipt by the first host of the resulting first type address response message from the first interface, retrieving the content of the response address field;

generating one or more packets for transmission having a header including
30 source and destination address fields, the source address field containing the address of the first host, and the destination address field containing the retrieved content of the response address field;

sending the or each generated packet to the first interface;

10069295.062502

for the or each said generated packet received by the first interface, accessing the stored mappings in accordance with the destination address of the received generated packet,

retrieving the stored interface address of the mapping whose retrieved

- 5 host address matches the destination address of the received generated packet,

generating an encapsulated packet having a payload formed by the received generated packet, and having a header including source and destination address fields, the source address field containing the address of the first interface, and the destination address field containing the retrieved interface network address,

- 10 sending the encapsulated packet to the second interface; and

for the or each encapsulated packet received by the second interface, un-encapsulating the received encapsulated packet to recover the original generated packet forming its payload, and

sending that recovered packet to the second host.

- 15 There may be included the step of storing the retrieved content in association with the name of the second host.

There may be included the steps of setting a time to live for the stored retrieved content, and rendering that stored retrieved content unuseable upon the expiry of the time to live, preferably deleting the stored retrieved content.

- 20 Protocol converters are known for enabling an IPv6 host to send messages to an IPv4 host. When a new IPv6 host is activated in an IPv6 domain, it employs the technique known as Neighbourhood Discovery (ND) to find out the identity of hosts with whom it can communicate directly. It broadcasts an ND message containing its IPv6 network address, and each host that receives it sends a reply
- 25 message containing that host's IPv6 network address. Since the domain uses an underlying transport mechanism, say Ethernet using media access control (MAC) addresses, each host receiving the ND message will retrieve the new host's IPv6 network address and also the MAC address of the new host, and the new host will retrieve from each reply message the sending host's IPv6 network address and its
- 30 MAC address.

The new host now constructs an ND table in which each entry corresponds with a neighbouring host and comprises a first part in the form of the 128 bit IPv6

address of that neighbouring host, and a second part in the form of the associated MAC address.

The interface device (containing the protocol converter) between that IPv6 domain and an adjacent IPv4 domain will also have received the ND message and sent a reply message, and the new host will have made a special Default entry in the ND table having its first part formed by 128 zeros (in variants, these are all ones) and its second part formed by the MAC address of that interface device.

Thus, when that new host wants to send a message to one of the other hosts in its domain, it constructs an IPv6 message and accesses its ND table to retrieve the MAC address associated with the destination address. The message is then encapsulated within an Ethernet packet in known manner and sent via the underlying Ethernet transport mechanism to the destination host.

If, on the other hand, the host constructs an IPv6 message having its destination address in the form of an IPv4-compatible or IPv4-mapped address, i.e. a message intended for an IPv4 host in the adjacent IPv4 domain, this destination address will not be found in the ND table. In this situation, the accessing algorithm will return the MAC address of the Default entry, and the message will be sent to the protocol converter.

Protocol converters can only convert (or translate) between corresponding fields of the headers of the IPv6 and IPv4 messages. Where a field in the header of, say, an IPv6 message has no corresponding field in the header of an IPv4 message, or vice versa, the information in that field will be lost in the protocol conversion process.

As mentioned above, tunnelling techniques are known for enabling IPv6 hosts to communicate amongst themselves when they are in spaced-apart domains. In this case, the interface device contains a tunnelling mechanism instead of a protocol converter. It will be appreciated that before now, for an IPv6 host to be able to communicate both with IPv4 hosts and with remote IPv6 hosts, it was necessary for that IPv6 host and the domain interface to be dual stack, i.e. having both IPv4 and IPv6 communication capability. If an IPv6 host was not dual stack, its accessing algorithm would return only a single MAC address for the Default entry. This would be the MAC address of the input port of a protocol converter, if the network administration had decided that the IPv6 host is to be able to communicate with

IPv4 hosts, or it would be the MAC address of the input port of a tunnelling mechanism, if the network administration had decided that the IPv6 host is to be able to communicate with IPv6 hosts. That Default entry MAC address could not be a common input address for both the protocol converter and the tunnelling
5 mechanism.

Methods of tunnel establishment in accordance with the present invention are advantageous in that the source host need only send a standard address request message in its own protocol, e.g. if the first network transmission protocol is IPv6 then that message will be an IPv6 DNS address request message, and the
10 establishment of the tunnel across the intervening IPv4 domain is automatic and completely autonomous, requiring nothing special from the source host. Thus, a company that has an existing IPv4 domain can make the transition from full IPv4 implementation to full IPv6 implementation by introducing isolated IPv6 domains using standard IPv6 technology.

15 Specific embodiments of the present invention will now be described with reference to the drawings in which:

Figure 1 is a schematic diagram of an IPv4 domain interfaced with two isolated IPv6 domains;

Figure 2 is a schematic diagram of a border router;

20 Figure 3 is a schematic diagram of an IPv6 DNS Response message;

Figure 4 is a schematic diagram of an IPv4 DNS Response message resulting from conversion of the IPv6 DNS Response message of Figure 3;

Figure 5 is a schematic diagram of an IPv6 DNS Response message resulting from conversion of the IPv4 DNS Response message of Figure 4; and

25 Figure 6 is a schematic diagram showing the format of special IPv6 addresses used with the 6to4 tunnelling technique.

In Figure 1, an IPv4 domain 10 separates a first IPv6 domain 12, constituting in accordance with the present invention a first network operating in accordance with a first transmission protocol and having network addresses in
30 accordance with a first addressing convention, from a second IPv6 domain 14, constituting in accordance with the present invention a third network also operating in accordance with the first transmission protocol and having network addresses in accordance with the first addressing convention. Hosts in the IPv4 domain 10 are

20090225.02502

IPv4 only, and hosts in the IPv6 domains 12 and 14 are IPv6 only. The IPv4 domain 10 constitutes in accordance with the present invention a second network operating in accordance with a second transmission protocol and having network addresses in accordance with a second addressing convention. For simplifying the drawings, no 5 IPv4 hosts are shown, and in each of the IPv6 domains 12 and 14 only one IPv6 host (28 and 30, respectively, as referred to later) is shown.

The first IPv6 domain 12 is connected to the IPv4 domain 10 via a border router 16A, also referred to as an ingress interface with respect to the first IPv6 domain 12 and constituting an interface of the present invention. The second IPv6 10 domain 14 is connected to the IPv4 domain 10 via a border router 16B, also referred to as an egress interface with respect to the first IPv6 domain 12. The border router 16B is identical to the border router 16A.

The IPv4 domain 10 contains a complete domain name system (DNS) 20 including a plurality of DNS servers 22, of which only two DNS servers 22A and 22B 15 are shown, and the IPv6 domains 12 and 14 contain respective DNS servers 24 and 26.

Suppose that a host 28 in the first IPv6 domain 12 wishes to send a packet to a host 30 in the second IPv6 domain 14. Thus, for this transaction, the host 28 is referred to as the source host 28 and the host 30 is referred to as the destination 20 host 30 .

The source host 28 knows the name of the destination host 30, so it constructs in known manner an IPv6 DNS Request message (not shown) requesting the IPv6 address of the destination host 30 . The source host 28 sends this DNS Request message as a recursive request to its local DNS server, which in this 25 embodiment is the DNS server 24. The DNS server 24 will, in known manner, send a number of iterative DNS Request messages (not shown) to the DNS 20 until it learns about the DNS server 26. Finally, a DNS Request message (not shown) will go to the DNS server 26 requesting the IPv6 address of the destination host 30. As the DNS request passes from the first IPv6 domain 12 through the border router 16A to the 30 IPv4 domain 10, it is processed by a protocol converter (PC) 32A (see Figure 2) and undergoes IPv6/IPv4 translation. Correspondingly, as the DNS request passes from the IPv4 domain 10 through the border router 16B to the second IPv6 domain 14, it is processed by a protocol converter 32B and undergoes IPv4/IPv6 translation.

1006665:02502

The protocol converters 32A and 32B conform to a specification known as Network Address Translation-Protocol Translation (NAT-PT). They translate between IPv4 and IPv6 addresses and keep state during the time of the session, and translation between IPv4 and IPv6 DNS Request messages and DNS Response 5 messages, including translation of IP headers and DNS payload information is controlled by an application layer gateway (ALG). In the art, an alternative term for a DNS Response message is a DNS Answer message.

For more detailed information the reader can obtain from the Internet Engineering Task Force (IETF), the document known as draft-ietf-ngtrans-natpt-10 05.txt, or any variant thereof, "Network Address Translation - Protocol Translation (NATPT)", by G. Tsirtsis and P. Srishuresh.

The DNS server 26 responds to the DNS Request message for the IPv6 address of the destination host 30 with a IPv6 DNS Response message 34 (see Figure 3) having a conventional format of destination address field 36, source 15 address field 38, and response address record 40 that contains the IPv6 address of the destination host 30.

This IPv6 DNS Response message 34 travels through the second IPv6 domain 14 to the border router 16B where it becomes converted to an IPv4 DNS Response message 42 (see Figure 4) comprising destination address field 44, source address 20 field 46, response address record 48 and, in accordance with the present invention, additional records 50 and 52, and this message 42 travels through the IPv4 domain 10 to the border router 16A where it becomes converted to an IPv6 DNS Response message 54 comprising destination address field 56, source address field 58 and response address record 60, and sent to the source host 28. The route that the DNS 25 Response message (in its various forms, i.e. 34, 42 and 54) takes in the domains 10, 12 and 14 depends on the DNS configuration in each of the domains, but it will have to pass through the border router 16B and the border router 16A in that order.

For convenience, the terms "field" and "record" are used synonymously and interchangeably in this description, although in the art a field is generally taken to be 30 a component part of a record.

When the IPv6 DNS Response message 34 is received by the border router 16B via its IPv6 network interface controller 62B, it is fed in parallel to the protocol converter 32B and to a controller 64B, and also to an encapsulator 86B and a 6to4

encapsulator 90B. The controller 64B is connected via a control line 65A to control inputs of the protocol converter 32B, the encapsulator 86B and the 6to4 encapsulator 90B and by placing a suitable address on the control line 65A selects the appropriate one of these devices.

- 5 The controller 64B (i) recognises that the received message is a DNS Response message and enables the protocol converter 32B, (ii) retrieves the IPv6 address from the response record 40 and writes this message to a storage location 66B formed by part of its internal memory 68B; (iii) writes the IPv4 address of the border router 16B, i.e. the IPv4 address of the tunnel terminating endpoint on the
- 10 border router 16B, to a storage location 70B also formed by part of its internal memory 68B; (iv) receives from the protocol converter 32B the converted DNS Response message 42; appends the content of the storage location 70B as the first additional record 50, and the content of the storage location 68B as the second additional record 52; and (v) sends the resulting IPv4 DNS Response message 42 to
- 15 an IPv4 network interface controller 72B for transmission over the IPv4 domain 10 to the border router 16A.

- In a variant, the received IPv6 DNS Response message 34 is fed only to the controller 64B, which writes this message to a storage location 74B formed by part of its internal memory 68B. The controller 64B then (i) retrieves the IPv6 address
- 20 from the response record 40 and writes this message to the storage location 66B; (ii) writes the IPv4 address of the border router 16B to the storage location 70B; (iii) generates a modified IPv6 DNS Response message by retrieving the content of the storage location 66B and appending the content of the storage location 70B as the first additional record 50, and the content of the storage location 66B as the second
- 25 additional record 52; and (iv) sends this modified IPv6 DNS Response message to the protocol converter 32B. The ALG of the protocol converter 32 processes only the header and address response record of the DNS Response message to produce the resulting IPv4 DNS Response message 42, i.e. it allows the additional records to remain unchanged.

- 30 It will be appreciated that the feeding of the received message directly to the protocol converter 32B, and the sending of an enabling signal on the control line 65A to the protocol converter 32B by the controller 64B is logically equivalent to the sending of the received message to the protocol converter 32B by the controller 64B

20250525 10:06:25

in the above variant, and constitutes sending the message to the protocol converter 32B in accordance with the present invention.

When the IPv4 DNS Response message 42 is received by the border router 16A via its IPv4 network interface controller 72A, it is fed in parallel to the protocol converter 32A and to a controller 64A.

The controller 64A (i) receives from the protocol converter 32A the output IPv6 DNS Response message comprising destination address field 56, source address field 58, response address record 60, and additional records 50, 52; and (ii) retrieves the IPv6 address from the second additional record 52, i.e. the true IPv6 address of the destination host 30, and inserts it into the response address record 60 of that output message instead of the IPv4-compatible IPv6 address for the destination host 30, which the protocol converter 32A had generated. The controller 64A then strips off the additional records 50, 52, and sends the resulting IPv6 DNS Response message 54 (see Figure 5) to an IPv6 network interface controller 62A of the border router 16A for transmission to the source host 28.

Additionally, the controller 64A is arranged to retrieve the IPv4 address of the tunnel terminating endpoint from the first additional record 50, to create a mapping of the IPv6 address of the destination host 30 to the address of the IPv4 tunnel terminating endpoint, and to store this mapping, i.e. create an entry, in an IPv6/tunnel endpoint table 76A formed by part of an internal memory 68A of the controller 64A. This table is referred to as a look-up table.

In a variant, the additional records 50, 52 are stripped from the DNS Response message prior to the retrieval of their contents. In another variant, the additional records remain attached to the DNS Response message, but this is not as efficient as stripping the additional records. In this present embodiment, each entry in the IPv6/tunnel endpoint table 76A comprises a first element 78A comprising the IPv6 address of a corresponding destination host 30, a second element 80A comprising the IPv4 address of the tunnel terminating endpoint, i.e. of the border router 16B, and third and fourth elements 82A and 84A, to be described later.

Upon receipt of the resultant IPv6 DNS Response message 54, the source host 28 retrieves the IPv6 address from its address record 60 and stores it in its internal memory for use in sending data packets to the destination host 30.

In known manner, the source host 28 generates for each of these data packets a header including a source address field and a destination address field, and writes the retrieved IPv6 address into the destination address field.

Upon receipt of each of these data packets at the border router 16A, the controller 64A retrieves the destination address, and, in accordance with the retrieved destination address, accesses the IPv6/tunnel endpoint table 76A. If there is a match with the contents of a first element 78A of an entry, the controller 64A retrieves the corresponding IPv4 tunnel terminating endpoint from the second element 80A of that entry, and commands an encapsulator 86A to encapsulate the packet in an IPv4 packet addressed to the border router 16B using the retrieved IPv4 tunnel terminating endpoint address. In this embodiment, the encapsulator 86A is arranged to receive the packet directly from the IPv6 network interface controller 62A of the border router 16A, but it does not perform encapsulation until commanded by the controller 64A. In a variant, the controller 64A receives the packet directly from the IPv6 network interface controller 62A and passes it to the encapsulator 86A if there is a match. In practice, when the border router 16A receives a packet the controller 64A writes it into a storage location of its internal memory 68A, and the controller 64A will pass to the encapsulator 86A the address of the relevant storage location, together with an instruction for the encapsulator 86A to access that storage location.

Upon receipt of the encapsulating IPv4 packet at the border router 16B, an un-encapsulator 88B of the border router 16B strips off the IPv4 header and retrieves the payload of that IPv4 packet, i.e. un-encapsulates the original IPv6 packet from the source host 28, and sends that IPv6 packet to the destination host 30. The controller 64B also creates a mapping (in its IPv6/tunnel endpoint table 76B) of the IPv6 address of the source host 28 and the tunnel originating endpoint, i.e. the IPv4 address of the originating border router 16A, these being respectively retrieved from the source address field of the IPv6 header and the source address field of the IPv4 header.

When the destination host 30 returns a Reply packet, a controller 64B of the border router 16B retrieves the destination address, "IPv6 host 28", from the received Reply packet, accesses its IPv6/tunnel endpoint table 76B in accordance with the retrieved destination address (i.e. seeking a matching element 78B),

retrieves the corresponding IPv4 address (element 80B), and commands an encapsulator 86B to encapsulate the Reply packet in an IPv4 packet addressed to an un-encapsulator 88A of border router 16A using the IPv4 tunnel originating endpoint address just retrieved from the element 80B of the IPv6/tunnel endpoint table 76B.

- 5 Upon receipt of this IPv4 packet at the border router 16A, the un-encapsulator 88A performs un-encapsulation to retrieve the Reply packet, and the border router 16A then sends the retrieved Reply packet to the source host 28.

The source host 28 and the destination host 30 are now in a session in which IPv6 packets pass between them via the tunnel just established between the 10 border routers 16A and 16B.

- The above described mechanism provides for an IPv6 host, which is in an isolated IPv6 domain, to communicate with another IPv6 host, which is in another isolated IPv6 domain, via an intermediate IPv4 domain, without any knowledge of where that other IPv6 host is, and without the source IPv6 host needing to do 15 anything different from a standard communication procedure with another IPv6 host within its own IPv6 domain. The DNS server local to the source IPv6 host makes a Request via the IPv4 domain to the IPv6 DNS server that is on the same network as the destination IPv6 host, and the border routers automatically set up respective mappings associating the tunnel endpoint and the IPv6 address of the IPv6 hosts 20 behind the border routers.

- In this embodiment, the host 28 stores the address retrieved from the DNS Response for a short time. The host 28 records the time at which the address is stored and deletes that stored address twenty four hours later. Alternatively, other methods can be employed, e.g. the address can be deleted at midnight, when the 25 day changes, or the address can be stored with a "time to live" value which is the start value of a count down timer. Similarly, the border router 16A deletes the entry in its IPv6/tunnel endpoint table 76A after a short time. By preventing permanent storage of the address of the host 30, this avoids the risk that the tunnel terminating endpoint becomes out of date for transmissions to the host 30, e.g. the border 30 router 16B is out of service, and that the border router 16A continues to send encapsulated packets to that out of date address. In a variant, the address is deleted after transmission of the last packet of the session. The intent of all the above

alternatives is, to a greater or lesser extent, to ensure that tunnels across the IPv4 domain 10 are always up to date.

In alternative embodiments, some of the entries in the IPv6/tunnel endpoint table 76A can be created by the administrative personnel of the network operator.

- 5 This is known as manual configuration of a tunnel, and the tunnel is permanent until changed at a later date by the administrative personnel.

- As shown in Figure 2, the border router 16A also comprises a 6to4 tunnelling encapsulator 90A (and 6to4 tunnelling un-encapsulator 92A) and can thus interwork with a border router which is similarly enabled, although in variants these
10 may be omitted. The special IPv6 addresses 94 (see Figure 6) used for this technique have a three-part format of which a first part 96 having thirty two bits is a prefix uniquely identifying that the packet is to be tunnelled by the 6to4 tunnelling technique, a second part 98 having thirty two bits is the IPv4 address of the 6to4 tunnel endpoint, and the third part 100 having sixty four bits is known as the
15 interface ID which is the modified MAC address of the destination host. In variants having a different tunnelling encapsulator, a different respective prefix is used for the same purpose.

- In some variants of these embodiments, the controller 64A is arranged to recognise the presence of this prefix within the retrieved destination address of a
20 received packet and to command the 6to4 tunnelling encapsulator 90A to handle the received packet, and in this case the 6to4 tunnelling encapsulator 90A is arranged to retrieve the special IPv6 address and to extract from its second part 98 the IPv4 address of the 6to4 tunnel endpoint.

- Where, as mentioned above, the controller 64A is arranged to perform prefix
25 recognition, the prefix to be recognised is stored in a storage location of its internal memory 68A, and this storage location can be an entry or part of an entry of the IPv6/tunnel endpoint table 76A.

- The un-encapsulators 88B and 92B have respective IPv4 addresses, which are used by the corresponding encapsulators 86A and 90A in generating their
30 respective encapsulated packets.

In the preferred arrangement of border router having a plurality of different encapsulators, e.g. 86, 90, the controller 64A accesses the IPv6/tunnel endpoint

table 76A in accordance with a set of match criteria to cover the range of possible situations. These are

- (a) a tunnel has already been established by the above described DNS Request technique and a IPv6 destination-specific IPv6/IPv4 entry exists in the IPv6/tunnel endpoint table 76A;
 - (b) a tunnel has already been established by one of the known tunnelling techniques and an IPv6/IPv4 entry exists in the IPv6/tunnel endpoint table 76A, of which the first element 78A has a first part in the form of a specific prefix corresponding to that tunnelling technique;
 - (c) network management personnel have manually configured the border router 16 to define a tunnel to a specific IPv6 destination host using 6to4 (or 6over4) to another border router (which might be the border router 16B or a different border router (not shown) associated with a further IPv6 domain (not shown)), and for this case the IPv6/tunnel endpoint table 76A has an entry whose first element 78A is the IPv4-compatible (or IPv4-mapped) address of that destination host;
 - (d) network management personnel have manually configured the border router 16A to define a tunnel to unspecified IPv6 destination hosts using 6to4 (or 6over4) to another border router (which might be the border router 16B or a different border router associated with a further IPv6 domain), and for this case the IPv6/tunnel endpoint table 76A has an entry having its first element 78A in the form of the 6to4 (or 6over4) prefix followed by the IPv4 address of that other border router followed by null characters, and in some variants the second element 80A of this entry contains null characters, whilst in yet other variants the second element 80A of this entry contains the IPv4 address of that other border router; and
 - (e) the table contains an entry whose first element 78A is a generic IPv4-compatible or IPv4-mapped IPv6 address, i.e. its first eighty bits are all zeros and the final thirty two (or in a variant, forty eighty) bits are null characters (zeros), the second and fourth elements 80A and 84A contain null characters, and a third element 82A contains the identifier "PC".
- The controller 64A uses its IPv6/tunnel endpoint table 76A to determine the appropriate handling of a received packet in the following manner.
- If the controller 64A finds an entry having a first element 78A matching the complete retrieved destination address, then the content of the second element 80A

1005025.02502

of that entry is retrieved and used as the IPv4 destination address, i.e. that of the border router 16B, the tunnel endpoint. Additionally, the content of the third element 82A of that entry is retrieved and used as a check that the retrieved IPv4 destination address and the packet received by the border router 16A are to be processed by the encapsulator 86A. The content of the third element 82A is either an identifier for an encapsulator 86A, 90A (e.g. "EN") or an identifier for the protocol converter 32A (e.g. "PC"). As a further check, the fourth element 84A of that entry contains an identifier for the encapsulation type. In other words, for an entry matching the complete retrieved destination address, as just described, the encapsulation type identifier will be "DNS" to signify that the encapsulator 86A is to be used.

If the controller 64A finds an entry whose first element 78A has the first thirty two bits matching the first thirty two bits, i.e. the special 6to4 prefix part, of the retrieved destination address, then the third and fourth elements 82A and 84A of that entry are checked ("EN" and "6to4", respectively), the IPv4 destination address is retrieved from the second element 80A of that entry and sent with the packet received by the border router 16A to be processed by the encapsulator 90A.

If the retrieved destination address is either IPv4-compatible or IPv4-mapped, i.e. the packet is to be protocol converted for an IPv4 destination, then its first eighty bits will be all zeros, and the following sixteen bits will be either all zeros if the address is IPv4-compatible, or all ones if the address is IPv4-mapped. Thus the controller 64A checks to see whether its IPv6/tunnel endpoint table 76A contains an entry whose first element 78A has its first eighty bits all zeros. The content of the second element 80A of such an entry will be all null characters, because no tunnel is involved, and the content of the fourth element 84A of such an entry will be all null characters, because no encapsulation is involved. The content of the third element 82A of that entry is retrieved and used as a check that the retrieved IPv4 destination address and the packet received by the border router 16A are to be processed by the protocol converter 32A. In this case, the content of the third element 82A is an identifier for the protocol converter 32A (e.g. "PC").

In other variants, the controller 64A is arranged to access the IPv6/tunnel endpoint table 76A, as before, and only command the 6to4 tunnelling encapsulator 90A upon detecting a match with an entry, and in this case the controller 64A passes the special IPv6 address to the 6to4 tunnelling encapsulator 90A, or

10069295.022502

alternatively the controller 64A extracts the IPv4 address of the 6to4 tunnel endpoint and passes it to the 6to4 tunnelling encapsulator 82A, or yet again the controller 64A, upon detecting such a match, retrieves the element 80A of the matching entry. This element 80A contains the IPv4 address of the 6to4 tunnel endpoint, which was inserted into that element 80A by the controller (or manually) upon creation of that entry.

In the above embodiment, the local DNS server for the source host 28 is the IPv6 DNS server 24, but in alternative embodiments it can be one of the IPv4 servers 22 of the DNS 20. In such alternative embodiments, although the host 28 can send a DNS Request message for obtaining the IPv6 address of the host 30 and, by the present invention, establish a tunnel across the IPv4 domain10, the situation is not symmetrical in that the host 30 cannot act as a source and establish a corresponding tunnel across the IPv4 domain10 to the host 28. For an IPv6 host to be contactable, i.e. act as destination, by the method of the present invention, it is necessary for the DNS server local to that IPv6 host to be an IPv6 DNS server on the same IPv6 domain as that IPv6 host, because the DNS Response message has to pass through the border router adjacent to that IPv6 host in order that the tunnel can be established. In other words, the DNS Request message has to pass through the IPv4 domain and not stop at an IPv4 DNS server acting as the local DNS server for the intended destination IPv6 host.

20060925:022502

CLAIMS

1. A method of establishing a tunnel from a first interface between a first network and a second network to a second interface between the second network and a third network, the first and third networks operating in accordance with a first transmission protocol and having addresses in accordance with a first addressing convention, and the second network operating in accordance with a second transmission protocol and having addresses in accordance with a second addressing convention, the tunnel being for the transport of messages from a first host on the first network to a second host on the third network, the method comprising the
- 10 steps of:
- sending from the first host an address request message in accordance with the first transmission protocol, referred to herein as a first type address request message, containing the name of the second host;
- upon receipt of the address request message at a name to address
- 15 conversion system of the third network, returning an address response message in accordance with the first transmission protocol, referred to herein as a first type address response message, and containing the address of the second host in a response address field;
- upon receipt of that first type address response message at the second
- 20 interface,
- converting it to an address response message in accordance with the second transmission protocol, referred to herein as a second type address response message, and
- augmenting that converted second type address response message by
- 25 fields respectively containing the address of the second interface in accordance with the second addressing convention and the address of the second host in accordance with the first addressing convention;
- and
- upon receipt of that augmented that converted second type address response
- 30 message at the first interface,
- converting it to a first type address response message,
- retrieving the contents of the augmenting fields,

storing at the first interface a mapping of the retrieved address of the second host and the retrieved address of the second interface for use in encapsulating messages from the first host addressed to the second host, and

5 replacing the content of the response address field of the resulting first type address response message by the retrieved address of the second host.

2. A method as claimed in claim 1, wherein for establishing a tunnel in the reverse direction for the transport of messages from the second host to the first host, the method comprises the further steps of:

upon receipt at the first interface of a message from the first host addressed to the second host, encapsulating that received message in accordance with the first mapping; and

15 upon receipt of the encapsulated message at the second interface, un-encapsulating that received encapsulated message, retrieving from the encapsulating header the address of the first interface in accordance with the second addressing convention, retrieving from the un-encapsulated message the address of the first host in accordance with the first addressing convention, and
20 storing at the second interface a mapping of the retrieved address of the first host and the retrieved address of the first interface for use in encapsulating messages from the second host addressed to the first host.

25

3. A method as claimed in either claim 1 or claim 2, including setting a time to live for a said stored mapping, and rendering that stored mapping unuseable upon the expiry of the time to live.

30 4. A method as claimed in claim 3, wherein the rendering step deletes that stored mapping.

10069245:022502

5. A method of sending packets from a first host on a first network via a second network to a second host on a third network, the first and third networks operating in accordance with a first transmission protocol and having addresses in accordance with a first addressing convention, and the second network operating in accordance with a second transmission protocol and having addresses in accordance with a second addressing convention, comprising the steps of:

establishing a tunnel from a first interface between the first network and the second network to a second interface between the second network and the third network in accordance with the method of claim 1;

10 upon receipt by the first host of the resulting first type address response message from the first interface, retrieving the content of the response address field;

generating one or more packets for transmission having a header including source and destination address fields, the source address field containing the address of the first host, and the destination address field containing the retrieved content of

15 the response address field;

sending the or each generated packet to the first interface;

for the or each said generated packet received by the first interface, accessing the stored mappings in accordance with the destination address of the received generated packet,

20 retrieving the stored interface address of the mapping whose retrieved host address matches the destination address of the received generated packet,

generating an encapsulated packet having a payload formed by the received generated packet, and having a header including source and destination address fields, the source address field containing the address of the first interface,

25 and the destination address field containing the retrieved interface network address,

sending the encapsulated packet to the second interface; and

for the or each encapsulated packet received by the second interface, un-encapsulating the received encapsulated packet to recover the original generated packet forming its payload, and

30 sending that recovered packet to the second host.

6. A method as claimed in claim 5, including the step of storing the retrieved content in association with the name of the second host.

10060297.022502

7. A method as claimed in claim 6, including the steps of setting a time to live for the stored retrieved content, and rendering that stored retrieved content unuseable upon the expiry of the time to live.

5

8. A method as claimed in claim 7, wherein the rendering step deletes the stored retrieved content.

9. A method of establishing a tunnel from a first interface between a first
10 network and a second network to a second interface between the second network and a third network, the method being substantially as hereinbefore described with reference to the drawings.

10. A method of sending packets from a first host on a first network via a
15 second network to a second host on a third network, the method being substantially as hereinbefore described with reference to the drawings.

2022-07-06 10:00:00

ABSTRACT
PACKET NETWORK INTERFACING

A method of establishing a tunnel across an IPv4 domain for the transport of packets
5 from a source host on one IPv6 domain to a destination host on another IPv6
domain, there being respective interfaces between the IPv4 domain and the IPv6
domains. The source host sends a normal IPv6 address request to its local DNS
server, which relays it to an IPv6 name server in the other IPv6 domain. The
response message, containing the true IPv6 address of the destination is received at
10 the remote interface, which appends to the resulting protocol converted DNS
response message a first additional record containing the true IPv6 address, and a
second additional record containing the IPv4 address of that interface. Upon receipt
at the near interface, the additional records are stripped off, their contents stored in
an entry of a table, and the true IPv6 address written into the address record of the
15 resulting IPv6 DNS response message. When the near interface receives a packet
from an IPv6 host, it checks whether the destination address matches an entry of its
table, and if so sends the packet to the encapsulator together with the IPv4 address
of the remote interface. The remote interface extracts the source address and the
address of the encapsulating interface and stores these in an entry in its
20 corresponding table for use in encapsulating return packets to the source. If,
however, the destination address is recognised as being of IPv4-compatible or IPv4-
mapped format, the packet is sent to a protocol converter.

Figure 2.

2025 RELEASE UNDER E.O. 14176




Fig.1




Fig. 2

10069295.022502




Fig. 3




Fig. 4




Fig. 5




Fig. 6

RULE 63 (37 C.F.R. 1.63)
DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

PACKET NETWORK INTERFACING

the specification of which (check applicable box(es)):

- ☐ is attached hereto
☐ was filed on _____

as U.S. Application Serial No. _____

(Atty Dkt. No. _____)

☒ was filed as PCT International application No. _____

PCT/GB00/03678

on 25 September 2000

and (if applicable to U.S. or PCT application) was amended on _____

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with 37 C.F.R. 1.56. I hereby claim foreign priority benefits under 35 U.S.C. 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed or, if no priority is claimed, before the filing date of this application:

Priority Foreign Application(s):

Application Number
99307550.6

Country
EUROPE

Day/Month/Year Filed
24 SEPTEMBER 1999

I hereby claim the benefit under 35 U.S.C. §119(e) of any United States provisional application(s) listed below.

Application Number _____

Date/Month/Year Filed _____

I hereby claim the benefit under 35 U.S.C. 120/365 of all prior United States and PCT international applications listed above or below and, insofar as the subject matter of each of the claims of this application is not disclosed in such prior applications in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose material information as defined in 37 C.F.R. 1.56 which occurred between the filing date of the prior applications and the national or PCT international filing date of this application:

Prior U.S./PCT Application(s):
Application Serial No. _____

Day/Month/Year Filed _____

Status: patented
pending, abandoned

PCT/GB00/03678

25 September 2000

PENDING

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon. And on behalf of the owner(s) hereof, I hereby appoint **NIXON & VANDERHYE P.C., 1100 North Glebe Rd., 8th Floor, Arlington, VA 22201-4714, telephone number (703) 816-4000 (to whom all communications are to be directed), and the following attorneys thereof (of the same address) individually and collectively owner's/owners' attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and with the resulting patent: Arthur R. Crawford, 25327; Larry S. Nixon, 25540; Robert A. Vanderhye, 27076; James T. Hoemer, 30184; Robert W. Faris, 31352; Richard G. Besha, 22770; Mark E. Nusbaum, 32348; Michael J. Keenan, 32106; Bryan H. Davidson, 30251; Stanley C. Spooner, 27393; Leonard C. Mitchell, 29009; Duane M. Byers, 33363; Jeffrey H. Nelson, 30481; John R. Bastova, 33149; H. Warren Burnam, Jr., 29366; Thomas E. Byrne, 32205; Mary J. Wilson, 32955; J. Scott Davidson, 33489; Alan M. Kagedo, 36178; Robert A. Molan, 29834; B. J. Sadoff, 36663; James D. Berquist, 34776; Updeep S. Gill, 37334; Michael J. Shea, 34725; Donald L. Jackson, 41090; Michelle N. Lester, 32331; Frank P. Presta, 19828; Joseph S. Presta, 35329. I also authorize Nixon & Vanderhye to delete any attorney names/numbers no longer with the firm and to act and rely solely on instructions directly communicated from the person, assignee, attorney, firm, or other organization sending instructions to Nixon & Vanderhye on behalf of the owner(s).**

1. Inventor's Signature: PETER HOVELL Date: 1st November 2000
Inventor: PETER HOVELL GB
(first) (last) (citizenship)
Residence: (city) WOODBRIIDGE (state/country) GREAT BRITAIN
Post Office Address: 24 MILL ROAD, NEWBOURNE, WOODBRIDGE, SUFFOLK
(Zip Code) IP12 4NP
2. Inventor's Signature: JOHN KING Date: 1/11/00
Inventor: JOHN KING GB
(first) (last) (citizenship)
Residence: (city) WOODBRIIDGE (state/country) GREAT BRITAIN
Post Office Address: 2 HERTFORDS PLACE, CHILLESFORD, WOODBRIDGE, SUFFOLK
(Zip Code) IP12 3SD

FOR ADDITIONAL INVENTORS, check box ☐ and attach sheet with same information and signature and date for each.

RULE 63 (37 C.F.R. 1.63)
DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION

Nixon & Vanderhye P.C. (12/95)

Page 2

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

3. Inventor's Signature: [Signature] Date: 1/11/2000
Inventor: JOHN PATTERSON GB
(first) MI (last) (citizenship)
Residence: (city) IPSWICH (state/country) GREAT BRITAIN
Post Office Address: THE ANNEXE, 5 THE MILLS, PLAYFORD ROAD, RUSHMERE ST ANDREW, IPSWICH, SUFFOLK
(Zip Code) IP4 5RL

1000005.02602

A25800UsSD